


# Diesel generator set K19 series



Specification sheet  
400 kWe, 500 kVA Prime



Our energy working for you.™

## Lowest life cycle cost

K19 series design features have made Cummins® diesel, the standard for comparison of operating economy, reliability and long life. When all cost factors like initial purchase, fuel, lube oil, maintenance and overhaul are considered, the bottom line will show that this **Cummins® 'K19 series'** will deliver the lowest life cycle cost.

## Heavy duty, durable and emission compliant

**Cummins® 'K19 series'** diesel engine comes with heavy duty features, bigger size camshaft, optimized turbo-matching, electrical STC injectors and is yet compact in size with optimum power to weight ratio making it the obvious choice for your long-term power needs.



The genset powered by the reliable **Cummins® 'K19 series'** diesel engine meets stringent exhaust emission tests as per MOEF norms without sacrificing fuel efficiency at normal operating loads.

## Silent Power

**Cummins® 500 kVA** enclosure is so designed as to have optimum performance and serviceability over the complete operating range. The enclosure is compact with integral fuel tank and is designed for ease in maintenance. The powder coated enclosure is manufactured on latest CNC machines to ensure superior finish and durability.

## Single source power assurance

Design, manufacture and testing of engine, alternator, enclosure and other accessories is done by Cummins Group of companies for that optimum performance integrity and is backed by countrywide product support network with single source responsibility for the entire package.

## Standard scope

Engine: Cummins® 'K19 series' direct injection, water cooled engine, 6 cylinder, in-line, 4 stroke, rated at 1500 RPM, conforming to ISO 3046 / BS 5514 has the following specifications:

- Cummins PT fuel pump
- Electrical Step Timing Control (ESTC) injector
- Holset turbocharger, pulse tuned exhaust manifold, stainless steel exhaust flexible connection
- Radiator or heat exchanger, coolant inhibitor, Low Temperature After cooling (LTA)
- Plate type lube oil cooler
- Full flow paper element filters - fuel, lube oil and by-pass
- Dry type replaceable paper element air cleaner with restriction indicator
- Flywheel housing & flywheel to suit single bearing alternator
- Starting motor – Electric, battery charging alternator
- First fill lube oil

PowerCom® controller: A Cummins manufactured microprocessor based genset controller for metering, monitoring, protecting and electronic governing of the engine.

Alternator: Stamford brushless alternator

- Self-excited, self regulated
- Class 'H' insulation
- Salient pole revolving field
- Single bearing
- Automatic voltage regulator

Accessories:

- Silencer suitably optimized to meet stringent sound emission standards laid down by MOEF / CPCB
- Base rail with integral fuel tank is provided with drain plug, air vent, inlet and outlet connection, level indicator, manhole etc.
- Sub-base fuel tank of 700 litres capacity
- 2 x 12 V dry, uncharged batteries with connecting leads and terminals

Acoustic enclosure:

- Specially designed to meet stringent MOEF/ CPCB norms of 75 dBA @ 1mtr at 75% load under free field conditions
- Designed to have optimum serviceability
- Air inlet louvers specially designed to operate at rated load even at 50 deg C enclosure temp.
- Made on special purpose CNC machines for consistency in quality and workmanship
- Powder coated for long lasting service life and superior finish
- With UV resistant powder coating, can withstand extreme environments
- Use of stainless steel hardware
- Insulation material meets exacting IS 8183 specs for better attenuation



PowerCom® features:

- Engine electronic governing
- Genset metering parameters like lube oil pressure, coolant temperature, engine speed (rpm), run hours, DC voltage, intake manifold temperature (wherever applicable), 3 phase volts and 3 phase amperes, frequency, kW, kVA, power factor

- Engine protection for low lube oil pressure, high coolant temperature (alarm and shutdown)
- Alternator protection parameters like under voltage, over voltage, over frequency, over current, under frequency (alarm and shutdown)
- Relay drivers for remote annunciations
- Cyclic cranking
- Auto/ manual start/ stop
- Alternator trim adjustment from the front key pad
- Model specific calibration from the front key pad
- Speed bias or raise/ lower inputs are provided for paralleling
- Remote monitoring capability through separate interface modules
- 6 configurable discrete outputs
- 2 configurable discrete inputs
- Smooth transition to rated speed
- Smart start algorithm
- Housed in a NEMA 3R/IP 53 non-metallic enclosure
- Operates within a wide temperature range (0-60 degrees C) and humidity up to 95%



Control panel: Powder coated control panel manufactured with 14 / 16 gauge CRCA sheet provides:

- MCCB /ACB of suitable rating with overload and short circuit protection
- Voltmeter and ammeter with selector switch
- KW / PF meters
- Frequency meter
- KWh meter
- Indicating lamps for "Load On" and "Set Running"
- Current transformers
- Aluminium busbars of suitable capacity with incoming and outgoing terminations
- Instrument fuses duly wired and ferruled

## Optionals

Engine: Heavy duty air cleaner, lube oil / coolant heater with thermostatic switch

Alternator: Thermistors, PMG excitation, space heater

Control panel: "PowerCommand® Control Panel (PCC 3100)" for microprocessor based governing, regulation, metering, monitoring and auto synchronising control system. AMF control panel, battery charger, remote/ auto start panel, auto/ manual synchronizing panel and audio/ visual annunciation for faults.

Others: Mobile sets with canopy

Our energy working for you.™

[www.cumminsindia.com](http://www.cumminsindia.com)

© 2007 | Cummins Power Generation | Specifications subject to change without notice  
Accessories shown are not part of standard equipment  
PGBU/CIL/003/K19 500 kVA/CPG/June 2007/1000



## Technical data

### Generator set specifications

Model	C 500 D5 P
Prime Power Rating kVA	500
Output Voltage and Frequency	415 Volts, 50 Hz
Power Factor	0.8 (lag)
No. of phases	3 phase

### Engine specifications

Make	Cummins
Model	KTA 19 G-9
No. of cylinders	6, in-line
Aspiration	Turbocharged-Aftercooled
Bore x Stroke	159 mm x 159 mm
Displacement	18.9 ltrs
Output - Prime	448 kWm
Fuel consumption @ 75% load with Radiator & Fan	77.4 ltr/hr
Fuel consumption @ 100% load with Radiator & Fan	101.8 ltr/hr
Typical lube oil consumption @ full load	0.12 ltr/hr
Total wet weight ( engine + radiator )	2687 kg
Length x Width x Height (engine)	1970 x 1092 x 1510 mm
Compression Ratio	13.9 : 1
Piston Speed	7.95 m/s
Governor / Class	Electronic / A1
Lubricating oil sytem capacity	55 ltrs
Coolant capacity (engine + radiator)	175 ltrs
Combustion air intake @ 100% load (+/- 5%)	32.7 m <sup>3</sup> /min
Fan air flow across radiator	1217 m <sup>3</sup> /min
Exhaust Temperature	538 °C
Battery Capacity / Rating	180 AH, 2 X 12 V

### Alternator specifications

Make	Stamford
Frame size / Model No.	HC5D
Voltage Regulation	± 1.0%
Insulation	Class H
Standard Enclosure	IP 23
Winding Pitch	2 / 3 Pitch
Stator Winding	Double layer lap
Rotor	Dynamically balanced
Wave form distortion	No load < 1.5%, non distorting balanced linear load < 5 %
Telephone Interference Factor	Better than 50
Total Harmonic Factor	Better than 2%

### Conformance standards

IS 4722, BS 5000, IEC 34 / 1, ISO 8528, BS 5514, ISO 3046

### Rating definition

- Prime power rating is applicable for supplying continuous electric power (at variable load) in lieu of commercially purchased power.
- Prime power is available for an unlimited number of hours per year in a variable load application.
- 10% overload is available for 1 hour in every 12 hours of operation.
- Rating definition is as per ISO 3046 / BS 5514
- Fuel consumption data is based on diesel having specific gravity of 0.85 and conforming to IS:1460/ Equivalent
- Fuel consumption tolerance is as per BS 5514

Our energy working for you.™


[www.cumminsindia.com](http://www.cumminsindia.com)

© 2007 | Cummins Power Generation | Specifications subject to change without notice  
PGBU/CIL/003/K19 500 kVA/CPG/June 2007/1000



## Typical enclosed genset dimensions\*

Genset Model	Rating (kVA)	Length (mm)	Width (mm)	Height (mm)	Weight (kgs.) (Dry)
C 500 D5 P	500 kVA	6500	2000	2300	8500



## Typical diesel genset dimensions

Genset Model	Rating (kVA)	Length (mm)	Width (mm)	Height (mm)	Weight (kgs.) (Dry)
C 500 D5 P	500 kVA	4001	1589	1905	4640

### Cummins Power Generation Offices:

Location:	Tel:	Fax:	Location:	Tel:	Fax:
Bangalore:	(080) 2361 3831/ 2361 1958	(080) 2361 4552	Indore:	(0731) 645 1042	
Chandigarh:	(0172) 506 3218	(0172) 266 3087	Jaipur:	(0141) 236 4944	(0141) 236 3746
Chennai:	(044) 2441 6429/ 2442 3412	(044) 2491 1120	Kolkata:	(033) 2287 8065/ 2247 2481	(033) 2290 3839
Delhi: Telefax:	(011) 4161 8357/ 61		Lucknow:	(0522) 278 6718/ 278 7514	(0522) 278 7880
Hyderabad:	(040) 2766 3017	(040) 2767 8892	Mumbai:	(022) 2756 6351/ 52/ 53/ 54	(022) 27566355
			Vadodara:	(0265) 232 4207/ 654 0390	(0265) 234 0623

Cummins India Limited  
 Power Generation Business Unit  
 35A/1/2, Erandawana,  
 Pune 411 038. India  
 Tel.: (91) 020-6602 7525  
 Fax: (91) 020-6602 8090

Authorised  
 Representative

Our energy working for you.™

[www.cumminsindia.com](http://www.cumminsindia.com)

© 2007 | Cummins Power Generation | Specifications subject to change without notice  
 Cummins and PowerCommand are registered trademarks of Cummins Inc.

\*Dimensions of the enclosure are excluding the silencer  
 Information contained in this publication is typical only and does not form part of any  
 contractual commitment

PGBU/CIL/003/K19 500 kVA/CPG/June 2007/1000

